

House amplifiers Medium power amplifiers

- built-in adjustable gain & slope regulators
- die-cast housing inside plastic case
- interstage switchable forward path gain allowing to reduce gain without affect noise figure of the amplifier

HA024

without return path

HA024R30

passive return path 30 MHz

HA024R65

passive return path 65 MHz





Tec	nnical	snecii	icai	ions

lechnical specifications				
TYPE	HA024	HA024R30	HA024R65	
Ordering number	02520	02521	02522	
Forward path				
Frequency range	47- 862 MHz		87- 862 MHz	
Gain, switchable*	18-20/27-30 dB (fixed slope pre-correction)			
Gain adjustment	17 dB			
Slope adjustment	17 dB			
Flatness*	±0.5 dB	±0.75 dB		
Input and output return loss	≥ 14 dB at 40 MHz; -1.5 dB/oct., but not less 10 dB			
Output level CTB, CSO (EN50083-3) $97~\mathrm{dB}\mu\mathrm{V}$				
Test point	- 30 dB bi-directional			
Noise figure	8.5 dB			
Return path				
Frequency range	-	5 - 30 MHz	5-65 MHz	
Gain	-	-1.5 dB	-2.5 dB	
Return loss	-	> 14 dB		
General				
Power consumption	230 V∼ 50/60 Hz 3.5 W			
Operating temperature range	-20° ÷ +50° C			
Dimensions/Weight (packed)	133x63x39 mm/0.36 kg			

^{*} for amplifier with return path measured 10 MHz after the starting frequency of forward path

