



CE 1471

MPT-350

REMOTE CONTROL KEYFOB

mpt-350_en 03/17

The MPT-350 keyfob enables you to operate the PERFECTA security system. Information on adding keyfobs and functions that can be run with their assistance is contained in the PERFECTA control panel manual.

1. Features

- Encrypted radio communication in the 433 MHz frequency band.
- 5 buttons to run up to 6 selected functions.
- Key press LED indicator.

2. Specifications

Operating frequency band	433.05 ÷ 434.79 MHz
Radio communication range (in open area)	up to 400 m
Battery	CR2032 3V
Environmental class according to EN50130-5	II
Operating temperature range.....	-10 °C...+55 °C
Maximum humidity	93±3%
Enclosure dimensions.....	38 x 78 x 16 mm
Weight.....	30 g

Hereby, SATEL sp. z o.o., declares that this keyfob is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC. The declaration of conformity may be consulted at www.satel.eu/ce

3. Battery replacement



There is a danger of battery explosion when using a different battery than recommended by the manufacturer, or handling the battery improperly.

Be particularly careful during installation and replacement of the battery. The manufacturer is not liable for the consequences of incorrect installation of the battery.

The used batteries must not be discarded, but should be disposed of in accordance with the existing rules for environment protection.

The battery life depends exclusively on how the keyfob is used. The more frequently the buttons are pressed, the higher the power consumption is. Each transmission sent from the keyfob contains information on the battery status. If the battery is low, pressing the button will make the LED flash once only (normally, the LED is flashing until the button is pressed, but not longer than for 30 seconds).

The figures below show how to replace the battery.

